Excel in Your Field

Specifications

CATEGORY	XR3135	XR3135H	XR3135C	XR3135HC	
ENGINE					
Туре	3Cyl. In-line Vertical, Water-cooled 4cycle Turbo Diesel, CRDI				
Model(Tier4)	L3C19-T				
Engine HP(Gross)	35				
PTO HP	30.1	28.0	30.1	28.0	
Rated speed, rpm	2,600				
Displacement-cu, in ³ .	114.7				
Fuel tank capacity, gal	10.6		1:	2.4	
Alternator(V-A)	12-70				
DRIVE TRAIN					
Transmission	Synchro shuttle / HST				
No. of Speed	F12 x R12 (GEAR) / 3 Ranges (HST)				
Brakes	Wet, Multi - disc				
Steering	Hydrostatic Power Steering				
PTO					
Туре	Independent				
Rear, rpm	540				
Mid PTO(Option)		2,000			
HYDRAULIC SYSTEM					
Control system		Position / Draft			
Implement pump, gpm		8.2			
Steering pump, gpm	4.1 (GEAR) / 5.5 (HST)				
Total flow, gpm	12.3 (GEAR) / 13.7 (HST)				
Category, 3pt hitch		C/	AT I		
Hitch Lift capacity, lbs(Hitch end)	1,808				
Remote valves	2 pairs				
DIMENSION					
Overall length, Bumper to link in.		124.3			
Overall width with tires, in.	60				
Wheelbase, in.	66				
Ht to top of rops, in.	(93	8	8.1	
TIRE SIZE					
Ag Front / Rear	7 - 14 / 11.2 - 24				
IND Front / Rear	25 x 8.5 - 14, 43 x 16 - 20				
Turf Front / Rear	25 x 8.5 - 14, 41 x 14 - 20				
WEIGHT					
Total weight without ballast, lbs.	3,219	3,285	3,589	3,655	

Note Specifications and design are subject to change without prior notice.

Get More Standard Features

- · Dry-type air cleaner
- Pre-heat starting aid
- Hand and foot throttle control Instrumentation-alternator
- · Warning and engine oil pressure light
- Remote control vales (2 pairs)
- Hydrostatic power steering

- · Front loader valve and joystick
- Hydraulic draft and position control
- Adjustable seat Extendable lower links and telescopic stabilizers
- Drawbar Turn signals
- · Safety flashers

Maximum Lift height, in. 92.7 Clearance with Attachment Dump, in. 61.7 Reach at Maximum Height, in. 15.0 48 Maximum Dump Angle, deg Maximum Rollback Angle, deg 43 Digging Depth, in. 4.9 49.1 Overall Height in Carry Position, in Lift Capacity(@ Pivot pin), lbs. 2.178 Breakout Force(@ Pivot pin), lbs. 3,450

LL3106 XR3100 Series

66

Backhoe	LB2104
Tractor Application	XR3100 Series
Digging Depth, in.	89.8
Reach from centerline of swing Pivot, in.	125.2
Loading Height, in.	72.4
Swing Arc, deg	180
Transport Height, in.	83.5
Bucket Rotating, deg	180
Stabilizer Spread(Down position), in.	68.7
Stabilizer Spread(Up position), in.	46.5
Bucket Digging force, lbs.	2,673

Additional Equipment on Cab Models

- Deluxe cabin with Heating and A/C
- · Cabin air recirculation

Front End Loader

Tractor Application Bucket Size. in.

· Interior lighting

Dealer Installed Options

- Mid PTO
- · Beacon lamp kit
- · Deluxe stereo system with CD Player, USB
- Room mirror
- Rear wiper
- Sun screen





P: 252.984.0700 | F: 252.984.0701 | www.lstractorusa.com

Dealer Imprint Zone

39000938-1504



XR3100 Series

XR3135 / XR3135H / XR3135C / XR3135HC **Premium Compacts**



- Eco-friendly TIER 4 35HP engine
- 5 year warranty*
- 12F x 12R fully synchronized shuttle shift or 3 range HST with cruise control
- Front wheel mechanical assist 4WD
- Choice of industrial, ag or turf tires at no additional cost
- Available with quick attach skid steer compatible front end loader with grill guard
- Available sub frame mounted, quick attach 7' backhoe
- Optional mid-mount PTO

*5-year limited warranty. See dealer for details

XR3100 Series Premium Compacts







Hydrostatic transmission models

Maximizes ease of use with effortless, clutchless and instant speed and directional changes with a simple push of the pedals



Flat platform

With rubber mat and side mounted gear lever, maximizes space, improves operator comfort, and makes getting on/off tractor easier



PTO switch

Turn the independent PTO on or off with a simple switch





New LS Tier 4 CRDI Engine

Meets EPA's most stringent emission standards while delivering rated horsepower quietly with low vibration



Provides accessibility for easy maintenance



2 sets of remotes and detent function standard

Adds functionality and improves ease of use by allowing attachment of hydraulically controlled implements without the high, additional costs like others in its class to add the remotes as options



Your choice of tires

Choose ag, industrial, ag or turf tires at no additional cost



Full function dash panel

Important functional data is available at a glance for optimum performance and control



Deluxe adjustable seat with retractable seat belt and arm rests

Keeps you safe and comfortable even during long operations