



LS Tractor



MT7 SERIES

MT7101CPS

PREMIUM UTILITY TRACTORS

6-YEAR LIMITED WARRANTY. SEE DEALER FOR DETAILS

MT7 SERIES

PREMIUM UTILITY TRACTORS




RECOMMENDED IMPLEMENTS/ ATTACHMENTS



LOADER:
High Capacity With An Abundance Of Standard Features



LAND GRADER:
Heavy Steel Construction, High Strength, Designed For Use In Demanding Applications



ROTARY CUTTER:
Durable Heavy Steel Design Providing Quality And Strength



BOX BLADE:
Features A Heavy Welded Steel Design For Use In Demanding Applications

FEATURES

- 6 Year Warranty*
- Available In 100.6 HP
- Cab Versions
- Unballasted Weight Up To 7,714 lbs.
- Premium Ergonomically Designed Cab
- 2 Sets Of Rear Remotes Standard With Float And Detent Functionality



High Capacity Loader
High Performing Lift Capacity, Among The Industry Leaders In Lift Height (139.9 in.)



Goodyear LSW Tires
Enable Better Traction, Less Field Compaction



Spacious Cab
Providing a Roomy Climate Controlled Working Environment



Standard Factory Grille Guard W/ Loader
Full Length Grille Guard Protects Body Panels And Radiator



Durability and Capacity
Heavy-Duty Frame And Lift Cylinders Enable Three-Point Lift Capacity Up To 5,139 lbs.



Power Shuttle Transmission
Provides Efficiency And Comfort In Demanding Applications (Standard)



Right-Side Cab Access
Enables Operators To Access Both Sides Of The Cab (Door And Steps)



Four Standard Rear Worklights
Provides Significant Illumination During Night Operation



Ergonomic Design
Provide Access To Controls For A Variety Of Applications

MT7101CPS

SPECIFICATIONS

CATEGORY	
ENGINE	MT7101CPS
Type	4 Cylinder, CRDI, Water-cooled
Model	F5G
Emission	Tier 4 Final
Engine HP (kW)	100.6 (75)
PTO (HP)	85.5
Rated Speed (rpm)	2,200
Displacement (in ³)	206.7
Fuel Tank Capacity (gal.)	30.4
DRIVE TRAIN	
Transmission Type (Option)	Power Shuttle
No. Of Speed	40 x 40
Forward Speed (mph)	0.1 - 22.6
PTO	
Type	Independent / Ground Speed PTO
Rear (rpm)	540 / 750 / 1,000
HYDRAULIC SYSTEM	
Control System	Position / Draft
Implement Pump (gpm)	15.7
Steering Pump (gpm)	6.5
Total Flow (gpm)	22.2
Category (3pt Hitch)	CAT II
Hitch Lift Capacity (lbs.)	8,378
Remote Ports	3 Pairs (Front) 2 Pairs (Rear)
DIMENSION	
Overall Length (Frame To Link, in.)	152.2
Overall Width With Tires (in.)	78.7
Wheelbase (in.)	90
Height To Top (in.)	105.4
Total Weight Without Ballast (lbs.)	7,714
TIRE SIZE	
Front / Rear R14	FW: 340/70R28, RR: 460/75R38
Front / Rear Ag	F: 13.6-24 R: 18.4-34

Note specifications and design are subject to change without prior notice.

FRONT END LOADER	LL8100
TRACTOR APPLICATION	MT7 SERIES
Bucket Size (in.)	83
Maximum Lift Height (in.)	139.9
Clearance With Attachment Dump (in.)	103.3
Reach At Maximum Height (in.)	23.4
Maximum Dump Angle (deg.)	57
Maximum Rollback Angle (deg.)	46
Digging Depth (in.)	4.6
Overall Height In Carry Position (in.)	68.8
Lift Capacity (At Pivot Pin) (lbs.)	5,139
Breakout Force (At Pivot Pin) (lbs.)	5,313
Approx. Weight (Loader W/O Bucket) (lbs.)	1,660

Additional Equipment Available

- Standard Air Suspension Seat With Swivel
- Standard Electric Engaged Independent PTO
- Instructor Seat
- Monitor Bracket
- Interior Power Source
- 3rd Rear Remote



LS Tractor

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

